
## SPECIFICATION SHEET



# Ø 2045mm 80.5in Ø 250mm 9.8in 50mm [2.0in]

## OPTION 1 (STANDARD) Surface Canopy

Remote power supply



## OPTION 2

Vertical wires x4 Round Flush Canopies Remote power supply No upcharge

## **OPTION 3**

Surface Canopy Integral power supply Upcharge applies

## **COVENANT ONYX 2000**

#### DESCRIPTION

Informed by the interlocking components of a snake's spine, Covenant is Lost Profile's contemporary take on a traditional chandelier.

### **MATERIALS**

Brass, Onyx, acrylic, LED.

DIMENSIONS

Diameter: 2045mm (80.5") Height: 216mm (8.5")

WEIGHT

70kg (154.3lbs)

LAMPING LED COLOUR TEMP LED strip

Warm White 3000k

2700k Available upon request

No upcharge

VOLTAGE/WATTAGE

12V DC @ 147W

LUMENS/CRI

11025lm @ 90+ CRI\* \*From the source

#### DRIVER

12V 150W 0-10V DIMMABLE

#### STANDARD FINISHES

Blonde Brass, Aged Brass, Dark Bronze (these finishes are waxed)

#### **CUSTOM SURFACE FINISHES**

Brushed Nickel, Chrome plating (Add 20%)

Clear enamel & powder coated finishes available on request (Add 10%)

## MAINTENANCE

All LOST PROFILE metal surfaces are waxed. These metal surfaces are designed to age and patinate. Wear gloves when handling to avoid hand prints.

## **CEILING CANOPY**

Option 1 - Standard: x1 Round Surface canopy (Remote)

Ø250 x 50mm (Ø9.8 x 2.0in).

Option 2 - Vertical Wires: x4 Round Flush canopies (Remote)

Ø100 x 6mm (Ø3.9 x 0.2in).

Option 3 - Surface Canopy: x1 Round Surface canopy (Integral)

Ø350 x 50mm (Ø13.8 x 2.0in). Upcharge applies.

COVENANT ONYX 2000 is supplied with 4 x 2000mm (78.8") suspension wires and 2000mm (78.8") of clear 2-core power cable.

Please advise us if you require longer suspension wires & power cable.

## INSTALLATION

Assembly required upon installing COVENANT as the Diffusers are supplied separately to the internal substrate ring.

Allow 1 hour for installing the Diffusers onto the ring. See installation guide for details.

#### **DRIVERS & DIMMING**

LOST PROFILE products are supplied with 0-10V dimmable LED drivers. PHASE & DALI Dimmable drivers are available for some regions, upon request. The location of the driver needs to be considered, whether in a ceiling cavity, in a wall cavity, or ideally in an accessible electrical cabinet.

## PRICING & LEAD TIMES

Please contact us or your nearest LOST PROFILE representative for current pricing and lead times.

