## SPECIFICATION SHEET


V3.0



# [7.9in] [15.7in] 6mm [.2in]

#### OPTION 1 (STANDARD)

Flush Canopy Remote power supply



## **OPTION 2**

Vertical wires x4 Round Flush Canopies Remote power supply No upcharge

## **OPTION 3**

Surface Canopy Integral power supply Upcharge applies

## **COVENANT ONYX CAPSULE 2400**

#### DESCRIPTION

Informed by the interlocking components of a snake's spine, Covenant is Lost Profile's contemporary take on a traditional chandelier.

#### **MATERIALS**

Brass, Onyx, acrylic, LED.

**DIMENSIONS** 

Length: 2445mm (96.3") Width: 945mm (37.2") Height: 216mm (8.5")

WEIGHT

60kg (132.3lbs)

LAMPING

LED strip

LED COLOUR TEMP

Warm White 3000k

2700k Available upon request

No upcharge

VOLTAGE/WATTAGE

12V DC @ 140W

LUMENS/CRI

10500lm @ 90+ CRI\*

DRIVER

12V 150W 0-10V DIMMABLE

#### STANDARD FINISHES

Blonde Brass, Aged Brass, Dark Bronze (these finishes are waxed)

#### **CUSTOM SURFACE FINISHES**

Brushed Nickel, Chrome plating (Add 20%)

Clear enamel & powder coated finishes available on request (Add 10%)

#### MAINTENANCE

All LOST PROFILE metal surfaces are waxed. These metal surfaces are designed to age and patinate. Wear gloves when handling to avoid hand prints.

#### **CEILING CANOPY**

Option 1 - Standard: x1 Flush canopy (Remote) 400 x 200 x 6mm (15.7 x 7.9 x 0.2in).

Option 2 - Vertical Wires: x4 Round Flush canopies (Remote)

Ø100 x 6mm (Ø3.9 x 0.2in). Option 3 - Surface Canopy: x1 Round Surface canopy (Integral)

Ø350 x 50mm (Ø13.8 x 2.0in). Upcharge applies. COVENANT ONYX CAPSULE 2400 is supplied with 4 x 2000mm (78.8") suspension

wires and 2000mm (78.8") of clear 2-core power cable.

Please advise us if you require longer suspension wires & power cable.

## INSTALLATION

Assembly required upon installing COVENANT as the Diffusers are supplied separately to the internal substrate ring.

Allow 1 hour for installing the Diffusers onto the ring. See installation guide for details.

### **DRIVERS & DIMMING**

LOST PROFILE products are supplied with 0-10V dimmable LED drivers. PHASE & DALI Dimmable drivers are available for some regions, upon request. The location of the driver needs to be considered, whether in a ceiling cavity, in a wall cavity, or ideally in an accessible electrical cabinet.

## **PRICING & LEAD TIMES**

Please contact us or your nearest LOST PROFILE representative for current pricing and lead times.

