

SPECIFICATION SHEET

V3.0



COVENANT PENDANT 1750

DESCRIPTION

Informed by the interlocking components of a snake's spine, Covenant is Lost Profile's contemporary take on a traditional glass chandelier.

MATERIALS

Brass, glass & aluminium

DIMENSIONS

Diameter: 1750mm (68.9")
Height: 144mm (5.7")

WEIGHT

65kg (143.3lbs)

LAMPING

LED strip

LED COLOUR TEMP

Warm White 3000k
2700k Available upon request
No upcharge

VOLTAGE/WATTAGE

12V DC @ 130W

LUMENS/CRI

9750lm @ 90+ CRI*
*From the source

DRIVER

12V 150W 0-10V DIMMABLE

STANDARD FINISHES

Blonde Brass, Aged Brass, Dark Bronze (these finishes are waxed)

CUSTOM SURFACE FINISHES

Brushed Nickel, Chrome plating (Add 20%)

Clear enamel & powder coated finishes available on request (Add 10%)

MAINTENANCE

All LOST PROFILE metal surfaces are waxed. These metal surfaces are designed to age and patinate. Wear gloves when handling to avoid hand prints.

CEILING CANOPY

Option 1 - Standard: x1 Hexagonal Flush canopy (Remote)

180 x 6mm (7.1 x 0.2in).

Option 2 - Vertical Wires: x1 Flush canopy + x3 Cable glider mounts (Remote)

Ø100 x 6mm (Ø3.9 x 0.2in).

Option 3 - Surface Canopy: x1 Round Surface canopy (Integral)

Ø350 x 70mm (Ø13.8 x 2.8in). Upcharge applies.

COVENANT 1750 is supplied with 4 x 2000mm (78.8") suspension wires and 2000mm (78.8") of clear 2-core power cable.

Please advise us if you require longer suspension wires & power cable.

INSTALLATION

Assembly required upon installing COVENANT as the glass is supplied separately to the internal substrate ring.

Allow 1 hour for installing the glass onto the ring. See installation guide for details.

DRIVERS & DIMMING



LOST PROFILE products are supplied with 0-10V dimmable LED drivers.

PHASE & DALI Dimmable drivers are available for some regions, upon request.

The location of the driver needs to be considered, whether in a ceiling cavity, in a wall cavity, or ideally in an accessible electrical cabinet.

PRICING & LEAD TIMES


Please contact us or your nearest LOST PROFILE representative for current pricing and lead times.



OPTION 1 (STANDARD)

Flush Canopy

Remote power supply




OPTION 2

Vertical wires

Remote power supply

No upcharge



OPTION 3

Surface Canopy

Integral power supply

Upcharge applies